Product data sheet

Specifications



To be discontinued

Data socket, Vivace, cat 5E, with shutter, 1 gang, aluminium silver

KB31RJ5E_AS

To be discontinued on: 30 June 2023

Main

Range	Vivace
Device short name	KB31
Product or component type	Data socket
Cover type	Shutter
Device application	Communication
Device presentation	Complete mechanism
Colour tint	Aluminium silver

Complementary

Connector type	M-110 keystone RJ45 connector
Communication network category	5e
Number of gangs	1 gang
Tightening torque	0.4 N.m
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	87 mm
Height	87 mm
Projecting depth	8 mm
Embedding depth	35 mm
Data socket type	RJ45 Cat.5e
Main colour tint	Aluminium silver

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Ambient air temperature for operation	-5…40 °C
Relative humidity	0…95 %
Environmental characteristic	Indoor use
Standards	FCC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	4 cm
Package 1 Length	8.6 cm
Package 1 Weight	84.1 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	19 cm
Package 2 Length	10 cm
Package 2 Weight	911 g
Unit Type of Package 3	CAR
Number of Units in Package 3	100
Package 3 Height	31.5 cm
Package 3 Width	50 cm
Package 3 Length	50 cm
Package 3 Weight	8660 g

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)