Product data sheet

Specifications



Socket, Vivace, universal, 3pin, 1 gang, white

KB426UEST_G19

Main

Range	Vivace
Product or component type	Socket-outlet
Device short name	KB426
Device application	Power supply
Device presentation	Complete mechanism
Outlet standard	Universal
Colour tint	White
Type of packing	Plastic bag
Socket number	1
Rated current	16 A Wall: white

Complementary

Integrated connection type	1 socket-outlet 220...250 V AC, maximum load current: 16 A
Outlet standard	Universal
Outlet poles configuration	2P + E with shutter
Number of gangs	1 gang
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screws
Fixing center	60.3 mm
Embedding depth	28 mm 16 A at 250 V AC, resistive
[Ue] rated operational voltage	220...240 V
Network frequency	50/60 Hz
Network type	AC

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contacts material	Brass and phosphor bronze
Connections - terminals	Screw terminals
Terminal identifier	L N E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm² 4 mm²
Width	86 mm
Surface treatment	Untreated
Height	86 mm
Surface finish	Glossy
Depth	37 mm
Number of terminals	3
Clamping connection capacity	2 x 2.5...2 x 4 mm² for rigid or stranded cable(s)

Environment

Standards	IEC 60884-1
Ambient air temperature for operation	-5…40 °C
Ambient air temperature for storage	-5…60 °C
Relative humidity	0…95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Recommended replacement(s)