Bảng **thông** số sản phẩm

Thông số kỹ thuật



Socket, Vivace, universal, 3pin, 13A, 250V, 2 gangs, white

KBT413S_WE

Ngừng sản xuất vào: 23 tháng một 2021

Ngừng cung cấp dịch vụ vào: 24 tháng một 2021

Bán dịch vụ hạn chế

Main

Range	Vivace
Product or component type	Socket-outlet
Device short name	KBT
Device application	Power supply
Device presentation	Complete mechanism
Outlet standard	Universal
Colour tint	White
Type of packing	Plastic bag
Socket number	2
Rated current	13 A Wall: white

Complementary

Integrated connection type	2 socket-outlet 220...250 V AC, maximum load current: 13 A
Outlet standard	Universal
Outlet poles configuration	2 x 2P + E with shutters
Number of gangs	2 gangs
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screws
Fixing center	120.6 mm
Embedding depth	25 mm
	13 A at 250 V AC, resistive
[Ue] rated operational voltage	220...240 V
Network frequency	50/60 Hz

Miễn trừ trách nhiệm: Tài liệu này không nhằm thay thế và không được sử dụng để xác định tính phù hợp hoặc độ tin cậy của các sản phẩm này cho các ứng dụng người dùng cụ thể

Network type	AC
Contacts material	Brass and phosphor bronze
Connections - terminals	Screw terminals
Terminal identifier	L N E
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm² 4 mm²
Width	146 mm
Surface treatment	Untreated
Height	86 mm
Surface finish	Glossy
Depth	33 mm
Number of terminals	6
Clamping connection capacity	1 x 2.5...3 x 2.5 mm² for rigid or stranded cable(s)

Environment

Ambient air temperature for operation	-5…40 °C
Ambient air temperature for storage	-5…60 °C
Relative humidity	0…95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.6 cm
Package 1 Width	3 cm
Package 1 Length	14.6 cm
Package 1 Weight	203.8 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.293 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	12479 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months

Thay thế được đề xuất